

ROOFINOX®

Like no other.

Roofinox FG

The seam sealant



Advantages at a glance

- A specially seam sealant for stainless steel and tinned stainless steel
- Effective and time-saving processing
- High adhesive power
- Seals all folded stainless steel roofs reliably

Technical information

- Suitable for transverse seams.
- Use in well-ventilated areas.
- Processing temperature -20°C to < +70°C.
- UV- and frost-resistant.
- Cut the nozzle Ø 3-5mm / at an angle of 45°.
- Close the seam after 48 hours at the latest, keep away water and moisture.
- One cartridge with 300 ml is sufficient for 25-30 m seams.

www.roofinox.com

Application Roofinox FG

The seam sealant



Equipment for the Roofinox seam sealant application:

- Roofinox FG
- Applicator
- Cartridge press
- Stanley knife

If an applicator is present: As a first step, remove the rubber ring from the applicator.



Then place the plastic ring from the applicator.

Be sure to insert the applicator first into the cartridge press.



First fix the rubber ring and then the plastic ring on the applicator.

Screw the nozzle on the cartridge. After that, cut the nozzle \varnothing 3-5mm, at an angle of 45 °.



Cut the cartridge with a knife.

Then insert the seam sealant in the cartridge press. Place the cartridge press with the applicator on the fold and apply the folding gel, \varnothing folding gel 4 mm.